mysql

- □□docker□□

```
docker pull mysql
```

- □□□□□□□□□

```
# MYSQL_ROOT_PASSWORD root□□
```

- □□□□□

```
/etc/mysql/my.cnf # □□□□
/var/lib/mysql    # □□□□
```

- `docker-compose.yaml` □□

```
version: '3'
services:
  mysql:
    image: mysql:5.7 # □□□□□□□□□□□□□□□□□□□□□□□□□□□□
    container_name: mysql-1
    privileged: true
    restart: always # □□□□
    ports:
      - 33309:3306
    volumes:
      - ./mysql:/var/lib/mysql                  # □□□□
      - ./my.cnf:/etc/mysql/conf.d/my.cnf # □□□□
    environment:
      - TZ=Asia/Shanghai
      - MYSQL_ROOT_PASSWORD=123456 # root□□
```

- my.cnf

```

[mysql]
user=root
```

```
default_character_set=utf8



[mysqld]
# □□□□□□□□□□
lower_case_table_names=1
# □□□□□□□□□□□□□□□□GROUP BY
sql_mode=STRICT_TRANS_TABLES,NO_ZERO_IN_DATE,NO_ZERO_DATE,ERROR_FOR_DIVISION_BY_ZERO,NO_AUTO_C
REATE_USER,NO_ENGINE_SUBSTITUTION

# □□□□□
max_connections=5000

# □□□□□□□□□□□□
wait_timeout=600

# mysql □□□□□□□□□□□□□□□□
interactive_timeout=600

# □□□□□□□□□□□□□□□1G,□□□□4M
max_allowed_packet=100M

# □□□ID□□□
server_id=1

# □□binlog
log_bin=binlog

# □□□□□□
relay-log=relay-bin

# □□□□□
binlog_format=ROW

# □□□□□□□□□
# read-only=1



# □□□□□□□
```

```
slow_query_log=1

# □□□□□□□□□
# slow_query_log_file=/var/log/mysql/mysql-slow.log
# □□□□□□□□□□ SHOW VARIABLES LIKE 'slow_query_log_file' □□

# □□□□□□□□□□30□□□
long_query_time=10
```

- □□□□

```
use mysql;
# □□□□
CREATE USER 'join_web_user'@'%' IDENTIFIED BY 'jo!n141421';

# □□□□
select * from user

# □□□□□□□
# □□ GRANT [privileges] on [databasename].[tablename] to ‘user’@‘host’
# privileges SELECT□INSERT□UPDATE,ALL
# databasename.tablename □□□□□□□□□□*□□*.*,databasename.*
# ‘user’@‘host’ □□□□□
GRANT all privileges ON *.* TO 'join_web_user'@'%'

# □□□□
flush privileges;

# □□□□
# □□ REVOKE [privileges]   ON [databasename].[tablename] from 'join_web_user'@'%'
# □□□□□□□□□□□□□□□
REVOKE all  ON *.* from 'join_web_user'@'%'

# □□□□
DROP USER 'join_web_user'@'%';
```

□□□ #10
□ □□□ □□□ 21 □□ 2023 05:19:29

□ □□□ □□□ 8 □□ 2026 09:21:56