



# tomcat

```
server:
  tomcat:
    max-connections: 10000 # 8192
    threads:
      max: 1000 # 200 tomcat 200
      min-spare: 100 #
    accept-count: 100 # 10%
```

- max-connections: 10000 Tomcat 10000
- threads:
  - max: 1000 Tomcat 1000
  - min-spare: 100 Tomcat 100

accept-count: 100 Tomcat 100

Timeout, socket closed

# nginx

gzip

```
# gzip
gzip on;
#
gzip_types text/plain text/css application/json text/javascript application/javascript;
#
gzip_min_length 1000;
# 1-9 CPU
gzip_comp_level 6;
# http header Vary: Accept-Encoding
gzip_vary on;
```

```
# 关闭E6gzip压缩
gzip_disable "MSIE [1-6] \.";

# 设置代理
gzip_proxied expired no-cache no-store private auth;

# 设置缓冲大小
gzip_buffers 16 8KB;

# 设置http版本
gzip_http_version 1.1;
```

## Springboot

- 
- 
- 

## jmeter

- jmeter.bat jar
- jmeter.bat

## HEAP

```
if not defined HEAP (
    rem See the unix startup file for the rationale of the following parameters,
    rem including some tuning recommendations
    set HEAP=-Xms1g -Xmx8g -XX:MaxMetaspaceSize=512m
)
```

## bat

```
if not defined JMETER_LANGUAGE (
    rem Set language
    rem Default to en_EN
    set JMETER_LANGUAGE=-Duser.language="zh" -Duser.region="CN"
)
```

从bat打开软件设置中文

#13

2025 08:19:20

2025 18:35:31