□□□□□□□□□&&tomcat□□

tomcat□□

```
server:
  tomcat:
    max-connections: 10000 # □□□□□□□□□8192□□□□□□□□□□□□
    threads:
      max: 1000 # □□□□□□□□□□□□□200□□tomcat□□□□□200
      min-spare: 100 # □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
    accept-count: 100 # □□□□□□□□□□□□□□□□□□□□
```

```
    # □□IE6□□gzip□□□□□□□□□□gzip□□
    gzip_disable "MSIE [1-6]\.";
    # □□□□□□□□□□□□□□□□□□□□
    gzip_proxied expired no-cache no-store private auth;
    # □□□□□□□□□□□16□8KB□□□□
    gzip_buffers 16 8k;
    # □□http□□□□□□□□□□□
    gzip_http_version 1.1;
```

Springboot□□□□□

- □□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□□□□□□□□□
- □□

jmeter□□□□

- □jmeter.bat□□□□□□□□□□□□jar
- □□jmeter.bat□□□□□□□□

□□HEAP□□□□□□□□□□□□□□

```
if not defined HEAP (
    rem See the unix startup file for the rationale of the following parameters,
    rem including some tuning recommendations
    set HEAP=-Xms1g -Xmx8g -XX:MaxMetaspaceSize=512m
)
```

□bat□□□□□□□□

```
if not defined JMETER_LANGUAGE (
    rem Set language
    rem Default to en_EN
    set JMETER_LANGUAGE=-Duser.language="zh" -Duser.region="CN"
)
```

从bat打开软件设置中文

jvm□□

https://iovhm.com/book/books/cee63/page/jvm

□□□ #15
□ □□□ □□□ 23 □□ 2025 08:19:20
□ □□□ □□□ 29 □□ 2026 16:40:23