linux□□nodejs□codex

□□□□

https://ws-264n30tcvp1at21s.cn-beijing.maas.aliyuncs.com/compatible-mode/v1

□□nodejs

```
# □□
# https://nodejs.org/zh-cn/download

wget https://nodejs.org/dist/v24.18.0/node-v24.18.0-linux-x64.tar.xz

# □□□
tar -xvf node-v24.18.0-linux-x64.tar.xz

# □□
mv node-v24.18.0-linux-x64 /usr/local/lib

# □□□□□□□□□
echo 'export PATH=/usr/local/lib/node-v24.18.0-linux-x64/bin:$PATH' >> ~/.bashrc
source ~/.bashrc
```

□□codex

```
# □□
npm install -g @openai/codex --registry=https://registry.npmmirror.com
```

□□ config.toml

```
mkdir -p /root/.codex
```

```
touch /root/.codex/config.toml
vi /root/.codex/config.toml
```

```
model_provider = "custom"
model = "qwen3.7-plus"
disable_response_storage = true
network_access = "enabled"

[model_providers.custom]
name = "custom"
wire_api = "responses"
requires_openai_auth = true
base_url = "https://dashscope.aliyuncs.com/compatible-mode/v1"
```

□□ auth.json

```
mkdir -p /root/.codex
touch /root/.codex/auth.json
vi /root/.codex/auth.json
```

```
{
  "OPENAI_API_KEY": "sk-************************8"
}
```

□□□ #6
□ □□□ □□□ 29 □□ 2026 15:52:40
□ □□□ □□□ 12 □□ 2026 04:45:39