nginx

- docker-compose.yaml

```
version: "3"
services:
  mobile-office-web:
    image: docker.io/nginx:latest
    restart: always # □□□□
    privileged: true
    ports:
      - 9095:80
    # volumes:
    #   - ./html:/usr/share/nginx/html
    #   - ./default.conf:/etc/nginx/conf.d/default.conf
    environment:
      - TZ=Asia/Shanghai
```

- default.conf

```
# touch default.conf

server {
    listen 80;
    #listen 443 ssl;
    server_name localhost;

    #charset koi8-r;
    #access_log  /var/log/nginx/log/host.access.log  main;

    #ssl_certificate     /home/ssl/server.crt;
    #ssl_certificate_key /home/ssl/server.key;
    #### □□□□ ####
    # □□gzip□□
    gzip on;
    # □□□□□□□□
    gzip_types text/plain text/html text/css application/json text/javascript
```

```
application/javascript;
    # □□□□□□□□□□□□□□□□□□□□□□□□□□□□
    gzip_min_length 1000;
    # □□□□1-9□□□□□□□□□□□□□□□□□□□□CPU
    gzip_comp_level 6;
    # □□□http header□□□Vary: Accept-Encoding□□□□□
    gzip_vary on;
    # □□IE6□□gzip□□□□□□□□□□□gzip□□
    gzip_disable "MSIE [1-6]\.";
    # □□□□□□□□□□□□□□□□□□□□□□□□□□□□
    gzip_proxied expired no-cache no-store private auth;
    # □□□□□□□□□□□□16□8KB□□□□
    gzip_buffers 16 8k;
    # □□http□□□□□□□□□□□□
    gzip_http_version 1.1;
    #### □□□□ ####

    #### □□□□ ####
    # □□□□□□□□
    add_header X-XSS-Protection "1; mode=block";
    # □□□□□□□□iframe□□frame□
    add_header X-Frame-Options "SAMEORIGIN";
    # □□□ HSTS (HTTP □□□□□□)
    add_header Strict-Transport-Security "max-age=31536000; includeSubDomains; preload";
    # □□□□□□□□□□□□□□□□ MIME □□□□
    add_header X-Content-Type-Options "nosniff";
    #### □□□□ ####

    root /usr/share/nginx/html;
    index index.html;

    location / {
        # □□□□□□□□VUE□□□□□□□□□
        add_header Cache-Control "no-cache no-store must-revalidate proxy-revalidate,max-
age=0";
        add_header Last-Modified $date_gmt;
        # □□□□□□□□□□□□
        etag off;
    }
```

```
    location /api/ {
        proxy_pass http://project-manager:8080;
        proxy_set_header Host $http_host;
    }
}
```

□□□□□□□GZIP

```
# □□□http□□□□□□□□□□server□□□□□□□□□□
server {
    #### □□□□ ####
    # □□gzip□□
    gzip on;
    # □□□□□□□□
    gzip_types text/plain text/html text/css application/json text/javascript
application/javascript;
    # □□□□□□□□□□□□□□□□□□□□□□□□
    gzip_min_length 1000;
    # □□□□1-9□□□□□□□□□□□□□□□□□□CPU
    gzip_comp_level 6;
    # □□□http header□□□Vary: Accept-Encoding□□□□□
    gzip_vary on;
    # □□IE6□□gzip□□□□□□□□□□gzip□□
    gzip_disable "MSIE [1-6]\.";
    # □□□□□□□□□□□□□□□□□□□□
    gzip_proxied expired no-cache no-store private auth;
    # □□□□□□□□□□□16□8KB□□□□
    gzip_buffers 16 8k;
    # □□http□□□□□□□□□□□
    gzip_http_version 1.1;
}
```

nginx□□□□□□□□□□□□

```
# □□□ server □□
server {

    # □□□□□□□□
    add_header X-XSS-Protection "1; mode=block";
    # □□□□□□□□iframe□□frame□
    add_header X-Frame-Options "SAMEORIGIN";
```

```
    # □□□ HSTS (HTTP □□□□□□)
    add_header Strict-Transport-Security "max-age=31536000; includeSubDomains; preload";
    # □□□□□□□□□□□□□□□□ MIME □□□□
    add_header X-Content-Type-Options "nosniff";
}
```

□□□ #8
□ □□□ □□□ 21 □□ 2023 05:17:11
□ □□□ □□□ 30 □□ 2026 17:44:57