

k8s redis

k8s redis redis

k8s nodeport hostport bug nodeport

docker-compose.yml

```
version: "3"
services:
  forward-redis-gzxfzd:
    image: harbor.iovhm.com/hub/rancher/klipper-lb:v0.1.2
    restart: always #
    container_name: forward-redis-gzxfzd
    privileged: true #
    ports:
      - 56300: 6379
    environment:
      - SRC_PORT=6379
      - DEST_PROTO=TCP
      - DEST_PORT=6379
      - DEST_IP=10.107.170.132
```

DEST_IP

k8s k8s curl pod ip ping

pod ip ip ip ip

- **1 IP**

```
kubectl get svc -n namespace_name
```

```

[root@101 forward-redis-gzxfzd]# kubectl get svc -n g
NAME                                TYPE           CLUSTER-IP      EXTERNAL-IP      PORT(S)          AGE
hardware-docking                   ClusterIP      10.107.233.246  <none>           10018/TCP        2d9h
jfast-auth                          ClusterIP      10.106.186.136  <none>           10001/TCP        2d9h
jfast-basic                         ClusterIP      10.102.202.100  <none>           10003/TCP        2d9h
jfast-devops-center                 ClusterIP      10.98.16.17     <none>           9530/TCP         2d9h
jfast-gateway                       ClusterIP      10.98.149.126  <none>           9527/TCP         2d9h
jfast-oa-services                   ClusterIP      10.99.11.37    <none>           10014/TCP        23h
jfast-property                      ClusterIP      10.108.194.188  <none>           10015/TCP        2d9h
jfast-public                        ClusterIP      10.100.71.147  <none>           10007/TCP        2d9h
jfast-research-center               ClusterIP      10.108.221.67  <none>           10019/TCP        23h
jfast-safety                        ClusterIP      10.105.80.193  <none>           10017/TCP        2d9h
jfast-talent                        ClusterIP      10.102.180.154  <none>           10016/TCP        2d9h
jfast-visitor                       ClusterIP      10.110.115.12  <none>           10013/TCP        2d9h
jfast-webui                         ClusterIP      10.97.37.173   <none>           80/TCP           25h
mysql                               ClusterIP      10.104.6.5     <none>           3306/TCP         2d9h
nacos-server                        ClusterIP      10.97.249.141  <none>           8848/TCP,9848/TCP 2d9h
ohd-server                          ClusterIP      10.98.235.232  <none>           8089/TCP,8843/TCP 2d9h
otter-server                        ClusterIP      10.107.136.158  <none>           8080/TCP         2d9h
redis                               ClusterIP      10.107.170.132  <none>           6379/TCP         2d9h

```

- 2个rancherIP

